


DLWP-001



SEE ROAD REPORT!
PHOTOMETRIC FILENAME: LM1041.RT8
POLAR GRAPH



Measurement Conditions: 4000°K, 1000lm, 40° Horizontal Angle, 0° Vertical Angle, 100°
#1 - Vertical Plane Through Horizontal Angles (0° - 180°) Through Axis, C.A.3 BLUE
#2 - Vertical Plane Through Horizontal Angles (0° - 180°) Through Axis, C.A.3 RED
#3 - Vertical Plane Through Horizontal Angles (0° - 180°) Through Axis, C.A.3 RED
#4 - Horizontal Plane Through Vertical Angle (0°) Through Axis, C.A.3 RED

Description 简述

- Fixture body (灯体): Die-cast aluminium.
Optical system (光学部件): Borosilicate glass lens frame.
Finishing (表面喷塑): Surface anti-ageing electrostatic spray processing, super resistance to corrosion.

基本性能 Characteristics:

类别 Performance	DLWP-001
防护等级 Safety type	IP65
外壳防腐性能 Housing's anti-corrosio property	Class II
防触电保护等级 Electric shock-proof rating	Class I
工作环境 Working environment	-35° ~ +45°C
功率及光源 Available power	30W LED module
额定电压 Rated voltage	AC 110V~277V
产品尺寸 Product size(Inch)	13.00"X9.00"X7.80"